

# Erosion control mat



NAUE GmbH & Co. KG  
 Gewerbestrasse 2  
 32339 Espelkamp – Fiestel  
 Germany

Phone: +49 57 43 – 41 - 0  
 Fax: +49 57 43 – 41 - 240

[info@naue.com](mailto:info@naue.com)

[www.naue.com](http://www.naue.com)

## Secumat® ES 601 G4

### Product description:

Three-dimensional erosion control mat consisting of an UV-stabilised extruded monofilament core and a woven fabric on one side

Property	Test method*	Unit	
Water flow rate q - at a load of 2 kPa - at a load of 200 kPa	EN ISO 12958	l/(m x s)	<i>i</i> = 1.0 13.8 0.6
<b>Erosion layer</b>			
Raw material	-	-	polypropylene (PP)
Mass per unit area	EN ISO 9864	g/m <sup>2</sup>	600
Thickness	EN ISO 9863-1	mm	20.0
<b>Open knitted</b>	<b>G4</b>	-	
Raw material	-	-	polyethylene (PE)
Mass per unit area	EN ISO 9864 (EN 965)	g/m <sup>2</sup>	30
Max. tensile strength, md / cmd**	EN ISO 10319	kN/m	≥ 2.0 / ≥ 0.4
Elongation at max. tensile strength, md / cmd**	EN ISO 10319	%	≥ 15 / ≥ 10
Roll dimension, width	-	m	2.00

\*based on, \*\*md = machine direction, cmd = cross machine direction

The listed technical values are guiding values, achieved in our laboratories and/or independent testing institutes. Our products are subject to changes without prior notice.